


目地部詳細図



呼び名	鉄筋											
	縦鉄筋①				縦鉄筋②				横鉄筋①		横鉄筋②	
	Q=1000		Q=2000		Q=1000		Q=2000		径	本数	径	本数
	径	本数	径	本数	径	本数	径	本数				
G250	D6	9	D6	18	D6	9	D6	18	4	11	4	3
G300A	D6	11	D6	22	D6	11	D6	22	4	11	4	3
G300B	D10	7	D10	14	D6	9	D10	14	D6	10	D6	2
G300C	D10	9	—	—	D6	9	—	—	D6	12	D6	2
G400A	D10	7	—	—	D6	11	—	—	D6	10	D6	2
G400B	D10	9	—	—	D6	11	—	—	D6	12	D6	2
G500A	D10	8	—	—	D6	13	—	—	D6	13	D6	3
G500B	D10	10	—	—	D6	12	—	—	D6	15	D6	3

呼び名	寸法 (mm)													参考重量 (kg)
	B	a	b	C	d	d'	e	f	h	H	T	r	Q	
G250	460	250	230	340	50	55	115	115	20	455	60	50	1000 (2000)	330 (660)
G300A	520	300	280	395	55	55	120	120	20	515	65	50		396 (792)
G300B	520	300	270	495	55	55	125	125	20	620	65	50		470 (940)
G300C	520	300	260	595	55	55	130	130	20	725	65	50		539
G400A	630	400	370	510	60	55	130	130	20	640	75	50		544
G400B	630	400	360	610	60	55	135	135	20	745	75	50		618
G500A	750	500	460	625	70	55	145	145	20	770	90	50		744
G500B	750	500	450	725	70	55	150	150	20	875	90	50		825

注 ()カッコ内は製品延長 Q=2000の場合